


Features

- Positive temperature coefficient for safe operation and ease of paralleling
- 175°C maximum operating junction temperature
- Extremely fast switching not dependent on temperature
- Essentially no reverse or forward recovery



Typical Applications

- Power converters
- Industrial motor drives
- Switching-mode power supplies
- Power factor correction modules

Part Number	Anode Metal	Cathode Metal	Packaging
UJD06550Z	Al (5μm)	Ti/Ni/Au (0.07/0.1/0.1μm)	Die on Tape

Descriptions

United Silicon Carbide, Inc offers the xR series of high-performance SiC Schottky diodes. With zero reverse recovery charge and 175°C maximum junction temperature, USCI's diodes are ideally suited for high-frequency and high-efficiency power systems with minimum cooling requirements.

Maximum Ratings

Parameter	Symbol	Test Conditions	Value	Units
DC Blocking Voltage	V_{DC}		650	V
Repetitive Peak Reverse Voltage, $T_j=25^\circ\text{C}$	V_{RRM}		650	V
Surge Peak Reverse Voltage	V_{RSM}		650	V
Maximum DC Forward Current ⁽¹⁾	I_F	$T_C = 100^\circ\text{C}$	50	A
Non-Repetitive Forward Surge Current ⁽¹⁾	I_{FSM}	$T_C = 25^\circ\text{C}$, 8.3ms Half Sine Pulse	TBD	A
Non-Repetitive Peak Forward Current ⁽¹⁾	$I_{F,max}$	$T_C = 25^\circ\text{C}$, 10μs	TBD	A
Non-Repetitive Avalanche Energy ⁽¹⁾	E_{AS}	$T_j = 25^\circ\text{C}$, L = 5mH, $I_{pk}=5.5\text{A}$, $V_{DD}=100\text{V}$	TBD	mJ
Maximum Junction Temperature	$T_{J,max}$		175	°C
Operating and Storage Temperature	T_j, T_{STG}		-55 to 175	°C

(1) Assumes a maximum junction-to-case thermal resistance of 0.65°C/W.

Electrical Characteristics

$T_J = +25^{\circ}\text{C}$ unless otherwise specified

Parameter	Symbol	Test Conditions	Value			Units
			Min	Typ	Max	
Forward Voltage	V_F	$I_F = 50\text{A}, T_J = 25^{\circ}\text{C}$	-	1.55	1.7	V
		$I_F = 50\text{A}, T_J = 150^{\circ}\text{C}$	-	2	2.1	
		$I_F = 50\text{A}, T_J = 175^{\circ}\text{C}$	-	2.1	2.25	
Reverse Current	I_R	$V_R = 650\text{V}, T_J = 25^{\circ}\text{C}$	-	135	500	μA
		$V_R = 650\text{V}, T_J = 175^{\circ}\text{C}$	-	270		
Total Capacitive Charge	Q_C	$V_R = 400\text{V}, I_F = 50\text{A},$ $di/dt = 250\text{A}/\mu\text{s}$		103		nC
Total Capacitance	C	$V_R = 1\text{V}, f = 1\text{MHz}$		1400		pF
		$V_R = 300\text{V}, f = 1\text{MHz}$		145		
		$V_R = 600\text{V}, f = 1\text{MHz}$		112		

Mechanical Characteristics

Parameter	Typical Value	Units
Die Dimensions (L x W)	2.00 x 4.00	mm
Top Anode Pad Opening (L x W)	1.78 x 3.78	mm
Wafer Size	100	mm
Anode Metallization (Al)	5	μm
Cathode Metallization (Ti/Ni/Au)	0.07/0.1/0.1	μm
Frontside Passivation BCB	5.5	μm
Die Thickness	100	μm

Disclaimer

United Silicon Carbide, Inc. reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. United Silicon Carbide, Inc. assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

United Silicon Carbide, Inc. assumes no liability whatsoever relating to the choice, selection or use of the United Silicon Carbide, Inc. products and services described herein.