


Description

United Silicon Carbide, Inc. offers the xR series of high performance SiC Schottky diodes. With zero reverse recovery charge and 175°C maximum junction temperature, USCi's diodes are ideally suited for high frequency and high efficiency power systems with minimum cooling requirements.



Part Number	Anode Metal	Cathode Metal	Packaging
UJ2D1215Z	Al 5μm	Ti/Ni/Au 0.07/0.1/0.1μm	Die on Tape

Features

- ◆ Positive temperature coefficient for safe operation and ease of paralleling
- ◆ 175°C maximum operating junction temperature
- ◆ Extremely fast switching not dependent on temperature
- ◆ Essentially no reverse or forward recovery
- ◆ RoHS compliant

Typical Applications

- ◆ Power converters
- ◆ Industrial motor drives
- ◆ Switching-mode power supplies
- ◆ Power factor correction modules

Maximum Ratings

Parameter	Symbol	Test Conditions	Value	Units
DC blocking voltage	V_R		1200	V
Repetitive peak reverse voltage, $T_j=25^\circ\text{C}$	V_{RRM}		1200	V
Surge peak reverse voltage	V_{RSM}		1200	V
Maximum DC forward current ⁽¹⁾	I_F	$T_C = 138^\circ\text{C}$	15	A
Non-repetitive forward surge current ⁽¹⁾ sine halfwave	I_{FSM}	$T_C = 25^\circ\text{C}, t_p = 10\text{ms}$	112.5	A
		$T_C = 110^\circ\text{C}, t_p = 10\text{ms}$	90	
Repetitive forward surge current ⁽¹⁾ sine halfwave, $D=0.1$	I_{FRM}	$T_C = 25^\circ\text{C}, t_p = 10\text{ms}$	51.2	A
		$T_C = 110^\circ\text{C}, t_p = 10\text{ms}$	31.3	
Non-repetitive avalanche energy ⁽¹⁾	E_{AS}	$T_j = 25^\circ\text{C}, L = 10\text{mH}, I_{pk}=5\text{A}, V_{DD}=100\text{V}$	132	mJ
Maximum junction temperature	$T_{J,max}$		175	°C
Operating and storage temperature	T_J, T_{STG}		-55 to 175	°C

(1) Assumes a maximum junction-to-case thermal resistance of 0.8°C/W.

Electrical Characteristics

$T_J = +25^\circ\text{C}$ unless otherwise specified

Parameter	Symbol	Test Conditions	Value			Units
			Min	Typ	Max	
Forward voltage	V_F	$I_F = 15\text{A}, T_J = 25^\circ\text{C}$	-	1.5	1.7	V
		$I_F = 15\text{A}, T_J = 175^\circ\text{C}$	-	2.5	3	
Reverse current	I_R	$V_R = 1200\text{V}, T_J = 25^\circ\text{C}$	-	45	375	μA
		$V_R = 1200\text{V}, T_J = 175^\circ\text{C}$	-	90	1000	
Total capacitive charge ⁽¹⁾	Q_C	$V_R = 800\text{V}$		69		nC
Total capacitance	C	$V_R = 1\text{V}, f = 1\text{MHz}$		730		pF
		$V_R = 400\text{V}, f = 1\text{MHz}$		64		
		$V_R = 800\text{V}, f = 1\text{MHz}$		51		
Capacitance stored energy	E_C	$V_R = 800\text{V}$		17.5		μJ

(1) See Figure 4, Q_C is independent on T_J , di_F/dt , and I_F as shown in the application note USCi_AN0011.

Typical Performance




Figure 1 Typical reverse characteristics




Figure 2 Typical forward characteristics




Figure 3 Capacitance vs. reverse voltage




Figure 4 Typical capacitive charge vs. reverse voltage




Figure 5 Typical capacitance stored energy vs. reverse voltage

Mechanical Characteristics

Parameter	Typical Value	Units
Die Dimensions (L x W)	2.62 x 2.62	mm
Top Anode Pad Opening (L x W)	2.32 x 2.32	mm
Wafer Size	100	mm
Anode Metallization (Al)	5	μm
Cathode Metallization (Ti/Ni/Au)	0.07/0.1/0.1	μm
Die Thickness	150	μm

Disclaimer

United Silicon Carbide, Inc. reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. United Silicon Carbide, Inc. assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

United Silicon Carbide, Inc. assumes no liability whatsoever relating to the choice, selection or use of the United Silicon Carbide, Inc. products and services described herein.