


## Description

United Silicon Carbide, Inc. offers the xR series of high performance SiC Schottky diodes. With zero reverse recovery charge and 175°C maximum junction temperature, USCi's diodes are ideally suited for high frequency and high efficiency power systems with minimum cooling requirements.

CASE



CASE



Part Number	Package	Marking
UJD06508TS	TO-220-2L	UJD06508TS

## Features

- ◆ Positive temperature coefficient for safe operation and ease of paralleling
- ◆ 175°C maximum operating junction temperature
- ◆ Extremely fast switching not dependent on temperature
- ◆ Essentially no reverse or forward recovery
- ◆ Enhanced surge capability
- ◆ RoHS compliant

## Typical Applications

- ◆ Power converters
- ◆ Industrial motor drives
- ◆ Switching-mode power supplies
- ◆ Power factor correction modules

## Maximum Ratings

Parameter	Symbol	Test Conditions	Value	Units
DC blocking voltage	$V_R$		650	V
Repetitive peak reverse voltage, $T_J=25^\circ\text{C}$	$V_{RRM}$		650	V
Surge peak reverse voltage	$V_{RSM}$		650	V
Maximum DC forward current	$I_F$	$T_C = 152^\circ\text{C}$	8	A
Non-repetitive forward surge current sine halfwave	$I_{FSM}$	$T_C = 25^\circ\text{C}, t_p = 10\text{ms}$	60	A
		$T_C = 110^\circ\text{C}, t_p = 10\text{ms}$	48	
Repetitive forward surge current sine halfwave, $D=0.1$	$I_{FRM}$	$T_C = 25^\circ\text{C}, t_p = 10\text{ms}$	34.5	A
		$T_C = 110^\circ\text{C}, t_p = 10\text{ms}$	21.5	
Non-repetitive peak forward current	$I_{F,max}$	$T_C = 25^\circ\text{C}, t_p = 10\mu\text{s}$	385	A
		$T_C = 110^\circ\text{C}, t_p = 10\mu\text{s}$	347	
Non-repetitive avalanche energy	$E_{AS}$	$T_J = 25^\circ\text{C}, L = 5\text{mH}, I_{pk}=4.9\text{A}, V_{DD}=100\text{V}$	67	mJ
Power dissipation	$P_{Tot}$	$T_C = 25^\circ\text{C}$	115	W
		$T_C = 152^\circ\text{C}$	17.6	
Maximum junction temperature	$T_{J,max}$		175	$^\circ\text{C}$
Operating and storage temperature	$T_J, T_{STG}$		-55 to 175	$^\circ\text{C}$
Soldering temperatures, wavesoldering only allowed at leads	$T_{sold}$	1.6mm from case for 10s	260	$^\circ\text{C}$

**Electrical Characteristics**

$T_J = +25^\circ\text{C}$  unless otherwise specified


Parameter	Symbol	Test Conditions	Value			Units
			Min	Typ	Max	
Forward voltage	$V_F$	$I_F = 8\text{A}, T_J = 25^\circ\text{C}$	-	1.5	1.7	V
		$I_F = 8\text{A}, T_J = 150^\circ\text{C}$	-	1.8	2.1	
		$I_F = 8\text{A}, T_J = 175^\circ\text{C}$	-	1.95	2.25	
Reverse current	$I_R$	$V_R = 650\text{V}, T_J = 25^\circ\text{C}$	-	20	230	$\mu\text{A}$
		$V_R = 650\text{V}, T_J = 175^\circ\text{C}$	-	40	700	
Total capacitive charge <sup>(1)</sup>	$Q_C$	$V_R = 400\text{V}$		18		nC
Total capacitance	C	$V_R = 1\text{V}, f = 1\text{MHz}$		260		pF
		$V_R = 300\text{V}, f = 1\text{MHz}$		29		
		$V_R = 600\text{V}, f = 1\text{MHz}$		23		
Capacitance stored energy	$E_C$	$V_R = 400\text{V}$		2.6		$\mu\text{J}$

(1) See Figure 8,  $Q_C$  is independent on  $T_J$ ,  $di_F/dt$ , and  $I_F$  as shown in the application note USCi\_AN0011.


**Thermal characteristics**

Parameter	symbol	Test Conditions	Value			Units
			Min	Typ	Max	
Thermal resistance	$R_{\theta JC}$			1	1.3	$^\circ\text{C}/\text{W}$

**Typical Performance**



**Figure 1 Typical reverse characteristics**



**Figure 2 Typical forward characteristics**




Figure 3 Power dissipation




Figure 4 Diode forward current




Figure 5 Capacitance vs. reverse voltage






Figure 6 Maximum transient thermal impedance



**Figure 7 Typical capacitance stored energy vs. reverse voltage**



**Figure 8 Typical capacitive charge vs. reverse voltage**

**Disclaimer**

United Silicon Carbide, Inc. reserves the right to change or modify any of the products and their inherent physical and technical specifications without prior notice. United Silicon Carbide, Inc. assumes no responsibility or liability for any errors or inaccuracies within.

Information on all products and contained herein is intended for description only. No license, express or implied, to any intellectual property rights is granted within this document.

United Silicon Carbide, Inc. assumes no liability whatsoever relating to the choice, selection or use of the United Silicon Carbide, Inc. products and services described herein.